



LANDSCAPE COLOR PLAN GROUND LEVEL



LANDSCAPE COLOR PLAN ROOF TOP LEVEL

All drawing and written materials herein constitute original work of the architect and may only be duplicated

> 230 N HIBISCUS DRIVE RESIDENCE

SEAL

LANDSCAPE ARCHITEC
RLA
DIEGO VANDERBIE
6200 S.W. 80 STREET
MIAMI BEACH, FLORIDA 3

NOT Released for Construction
Date
Job Number
Drawing History

1 Landscape 91/17/202
No. Issue Date

LANDSCAPE COLOR PLANS

heet

Submittal Design Review Board Submi Date: 01/31/2024

LANDSCAPE NOTES

- 1. ALL PLANT MATERIAL SHALL BE FLORIDA GRADE NO. 1 OR BETTER.
- CONTRACTOR SHALL BECOME FAMILIAR WITH THE LOCATION OF, AVOID, AND PROTECT ALL UTILITY LINES, BURIED CABLES, AND OTHER UTILITIES.
- TREE, PALM, ACCENT AND BED LINES ARE TO BE LOCATED IN THE FIELD AND APPROVED BY THE LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- 4. ANY CHANGES TO R.O.W. (RIGHT OF WAY) MATERIAL IN REGARDS TO PLACEMENT OF SPECIES SHALL REQUIRE THE APPROVAL AND CONSULTATION OF THE CITY URBAN FORESTER AND OR CITY STAFF.
- ALL PLANTING SOIL SHALL BE 50:50 TOPSOIL:SAND MIX, FREE OF CLAY, STONES, ROCKS, OR OTHER FOREIGN MATTER. THIS SPECIFICATION INCLUDES ALL BACKFILL FOR BERMS AND OTHER LANDSCAPE AREAS.
- 6. CARE SHALL BE TAKEN TO AVOID PLACEMENT OF CONSTRUCTION FILL, GRAVEL, AND OR DEBRIS OVER THE ROOTBALLS OF INSTALLED OR EXISTING TREES AND OR PALMS ON SITE.

SODDED-LAWN AREAS
2" DEPTH PLANTING SOIL SPREAD IN PLACE-THROUGHOUT.

GROUNDCOVER PLANTING BEDS: 6" DEPTH PLANTING SOIL SPREAD IN PLACE- THROUGHOUT.

SHRUB AND HEDGE PLANTING AREAS: 12" DEPTH PLANTING SOIL SPREAD IN PLACE-THROUGHOUT.

TREES, PALMS, SPECIMEN PLANT MATERIAL LOCATIONS:
REMOVE ALL LIMEROCK PRESENT TO A DEPTH OF AT LEAST 30" BEFORE PLACING NEW
PLANTING SOIL. APPLY NEW CLEAN PLANTING SOIL IN PLANTING AREA AS REQUIRED

LANDSCAPE ISLANDS AND BUILDING FOUNDATIONS:
EXCAVATE AND REMOVE ALL LIMEROCK, ROCKS, DEBRIS, ETC. TO A DEPTH OF 12" AND
BACKFELL W 50-50 TOPSOLS-AND MIX. BUILDING FOUNDATIONS SHALL BE THE SAME
DEPTH TO A WIDTH OF 36" FROM THE BUILDING BASE.


- THE SITE CONTRACTOR SHALL BE RESPONSIBLE TO BRING ALL GRADES TO WITHIN 2° OF FINAL GRADES. THIS SHALL INCLUDE A 2° APPLICATION OF 50:50 TOPSOIL:SAND MIX FOR ALL LANDSCAPE AND AREAS TO BE SOIDDED.
- THE LANDSCAPE CONTRACTOR SHALL CALCULATE AND SUBMIT AN ITEMIZED PRICE FOR THE 2"APPLICATION OF 95.90 MIX FOR ALL SOD AREAS AS A REFERENCE IN THE CASE. THAT THERE WOULD BE A DISCREPANCY BETWEEN SITE AND LANDSCAPE CONTRACTORS AND NOTIFY THE SITE CONTRACTOR OR PROJECT SUPERINTENDENT AS TO THIS DISCREPANCY. IT WILL THEN BE DETERMINED WHICH PARTY WILL PROVIDE THIS 2"TOPSOIL.SAND APPLICATION AND SUBSEQUENT PAYMENT.OTHER PLANTING SOIL MIXES TO BE ADDED, I.E. FOR TREES, PARMS, SPECIMEN PLANTS, SHOULDE AND GROUNDCOVERS SHALL BE THE RESPONSIBILITY OF THE LANDSCAPE CONTRACTOR AND BE INCLUSIVE WITH THE LANDSCAPE IN THE STATE OF THE S
- ALL EXISTING TREE + PALM INFORMATION THAT HAS BEEN PROVIDED ON THIS PLAN FOLLOWS THE MAMILE BACH COUNTY ET AM. TREE PERMITTING GUIDELINES, ANY TREES PROHIBETED SPECIES LIST 2444 (IMAY NOT BE SHOWN FOR CLARITY PURPOSES. ANY DISCREPANCIES IF NOTED UPON FURTHER RIELD INSPECTION SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE LANDSCAPE ARCHITECT.
- IRRIGATION SHALL PROVIDE FOR A 100% COVERAGE WITH 50% OVERLAP MINIMUM AND BE PROVIDED BY A FULLY AUTOMATIC IRRIGATION SYSTEM WI RAIN MOISTURE SENSOR ATTACHED TO CONTROLLER. ALL FORIDA BUBLIONS CODE APPENDIX F** IRRIGATION REQUIREMENTS SHALL BE STRICTLY ADHERED TO FOR INSTALLATION AND PREVAILING WATER MANAGEMENT DISTRICT RESTRICTIONS AND REQUILATIONS SHALL BE IN COMPLIANCE FOR POST-INSTALLATION WATERINGS SCHEDULES CONTRACTOR SHALL COORDINATE WITH THE RIRRIGATION CONTRACTOR AND LEXCE PROVISIONS FOR ALL SLEEVING AND PIPE ROUTHING ALL UNDERGROUND UTILITIES TO BE LOCATED BY DIALING SIT AS REQUIRED BY LAW.


- 1. ALL SYSTING TREE PALIN INFERNATION THAT HAS SEEN PROVIDED ON THE PALAN
 PALICAINEN HE MAIN BECACH COMINT EAM. THE PRINNITING OUDELINES MAY THEES OF
 PALINS CONSIDERED INVASIVE OR THAT FALLS LINDER THE TREE PERMIT EXEMPTION. I
 PROHIBITIES SPECIES LIST 244 (4) MAY NOT BE SOOMN FOR CLARITY PURPOSES. ANY
 DISCREPANCIES IF NOTED UPON FURTHER FIELD INSPECTION SHALL BE BROUGHT TO
 THE IMMEDIATA ATTENTION OF THE LANDSCAPE ARCHITECT.
- 12. ALL PLANTING BEDS SHALL BE MULCHED TO A DEPTH OF 2' WITH A SMALL GRAY GRANTE AGGREGATE OF APPROVED ORGANIC MULCH FIRE FROM WEEDS AND PESTS. NO CYPRESS MULCH OR 'RED DYB MULCH OF YEA EXCEPTED. KEEP MULCH 3' AWAY FROM TREE OR PALM TRUNKS AS PER INDUSTRY RECOMMENDATIONS.
- 13. SOD SHALL BE 'EMPIRE TURP' ZOYSIA GRASS IN ALL LAWN AREAS AS SHOWN ON THE PLANS. SOD SHALL BE STRONGLY ROOTED, FREE FROM WEED, FUNGUS, INSECTS AND DISEASE. CONTRACTOR SHALL SOO ALL AREAS AS INDICATED ON THE PLANS OR AS DIRECTED. PAYMENT SHALL BE DETERMINED BY THE TOTAL MEASURED SODED AREAS X THE UNIT PRICE SUBMITTED AND FIELD VERFIELD. SOD SHALL CARRY A S-MONTH
- ALL TREES, PALMS, SHRUBS AND GROUNDCOVERS, AND SOD / LAWN SHALL CARRY A ONE-YEAR WARRANTY FROM THE DATE OF FINAL ACCEPTANCE.
- 14A. MAINTENANCE: ALL NEWLY INSTALLED PLANTING MATERIAL WILL BE MAINTEINDED IN A CONDITION THAT MEETS OR EXCEEDS FLORIDA GRADE #01 AND HAS A (01) YEAR REPLACEMENT
- GUARANTEE

 ALL TREES AND PALMS SHALL BE STAKED PER ACCEPTED STANDARDS BY THE FLORIDA
 NUBSERYMEN A GROWERS LANDSCAPE ASSOCIATION (FNGLA) AND ANSIA-300 (PART
 6)-2012 TREE, SHRUB, AND OTHER WOOD'S PLANT MANAGEMENT STANDARD PRACTICES
 (PLANTING AND TRANSPLANTING). CONTRACTOR SHALL ENSURE THAT THE PLANS;
 DETAILS, SPECIFICATIONS AND NOTES HAVE BEEN ADHERED TO AND THAT THE
 LANDSCAPE AND IRRIGATION INSTALLATION IS COMPLIANT TO ALL ITEMS AS DIRECTED
 ON THE PLANS PRIOR TO SCHEDULING OF THE FIRMA. IMPRECTION.

CONTRACTOR SHALL REMOVE ALL STAKES, POLES, WELLINGTON TAPE AND OR BRACING MATERIALS FROM ALL PALMS, TREES AND SHRUBS WITHIN 1 YEAR OF INSTALLATION.

- THE PLANT LIST IS INTENDED ONLY AS AN AID TO BIDDING. ANY DISCREPANCIES FOUND BETWEEN THE QUANTITIES ON THE PLAN AND PLANT LIST, THE QUANTITIES ON THE PLAN SHALL BE HELD VALID.
- IF NECESSARY, CONTRACTOR SHALL PROVIDE A WATER TRUCK DURING PLANTING TO ENSURE PROPER WATERING-IN DURING INSTALLATION AND CONTRACTOR WILL BE RESPONSIBLE FOR CONTINUAL WATERING UNTIL FINAL ACCEPTANCE BY THE OWNER. A MINIMUM OF 6 MONTHS OF SUPPLEMENTAL HAND OR AUTOMATIC IRRIGATION SYSTEM WATERING SHALL BE REQUIRED TO AID IN NEW TREE OR PALM
- FERTILIZATION: ONE COMPLETE APPLICATION OF GRANULAR FERTILIZER SHALL BE APPLIED PRIOR TO FINAL ACCEPTANCE AND APPROVAL BY THE LANDSCAPE ARCHITECT. FERTILIZER SHALL BE OSMACOTE OR APPROVAL EQUAL.
- SHOULD ANY TREES OR PAINS SE DAMAGED THEY SHALL BE EVALUATED BY THE CITY STAFT TO DETERMINE CORRECTIVE ACTIONS THAT MAY INCLUDE REMOVAL. ORRECTIVE PRUNING AND OR REPLACEMENT. ANY CORRECTIVE ACTION REQUIRED SHALL BE PERFORMED IN ACCORDANCE WITH A MIAMI BEACH COUNTY CODE. ANSI-A 300 PRUNING STANDARDS AND OR AN ISSUED ERM THEE PERMIT OR ENVIRONMENTAL PERMIT. ANY CORRECTIVE PRUNING SECULIRED SHALL BE PERFORMED BY AN ISA CERTIFIED ARROWNEST OR ASCA CONSULTING ARBORIST
- 3. ALL TREES + PALMS TO REMAIN OR BE RELOCATED ON SITE IN THE VICINITY OF CONSTRUCTION ACTIVITIES, SHALL BE PROTECTED THROUGH THE USE OF TREE PROTECTION BARRICAGES INSTALLED AT THE TESTE OF PALM DRIP LINE A TREE PROTECTION FENCE SHALL BE CONSTRUCTED PRIOR TO ANY CONSTRUCTION AC INCLUDING RESIDENCE AND SHALL REMAIN IN PLACE UNTIL ON SITE CONSTRUCTION ESTECONSTRUCTION BEEN COMPLETED.






GROUNDCOVER PLANTING DETAIL

SINGLE LEADER, NO CO-DOMINANT LEADERS, NO INCLUDED BARK. BLACK WELLINGTON' TAPE OR APPROVED EQUAL GUYS, 3' TREE, SPACED EQUALLY AND LOCATED ABOVE THE FIRST LATERAL BRANCHES GTON TAPE OR GUYS TO BE CLEARLY MARKED W/ REMOVE BURLAP FROM THE TOP X OF THE ROOTBALL. - PLANT TOP OF ROOTBALL EVEN WITH FINISHED GRADE.
PLANTING PIT TO BE TWICE THE DIAM. OF ROOTBALL PROTECT STAKED END OF WELLINGTON TAPE W/ A 12" LONG SECTION OF PVC PIPE (TYP.) PROVIDE 2" X 4" X 18" LENGTH WOOD BATTENS AS NECESSARY TO SUPPORT WOOD BRACES BACKFILL AROUND THE ROOTBALL WITH 50:50 TOPSOIL:SAND MIX.

TREE PLANTING DETAIL

PROTECTION DETAIL NOTE
CONTRACTOR TO INSTALL PRO


TREE / PALM PROTECTION DETAIL



- 2" MIN. SAUCER COLLAR FOR WATER RETENTION

PLANTING SOIL MIX - SEE LANDSCAPE NOTES, FOR MIX, DEPTH, ETC.

SHRUB PLANTING DETAIL



PALM TRANSPLANT DETAIL

3" RECYCLED MULCH OR APPROVED EQUAL, PULL MULCH 2" BACK FROM TRUNK, FORM SAUCER 4"6" ALL AROUND PLANTING HOLE. - PLANT TOP OF ROOTBALL EVEN WITH FINISHED GRAD REMOVE BURLAP FROM TOP X OF THE ROOTBALL PLANTING PIT TO BE TWICE THE DIAM. OF ROOTBAL BACKFILL AROUND THE ROOTBALL WITH 50:50 TOPSOIL:SAND MIX PLACE ROOTBALL AT THE BOTTOM OF THE

PALM PLANTING DETAIL

All drawing and written

DRIVE E 230 N HIBISCUS RESIDENCI

SEAL

LANDSCAPE NOTES

L-2.0 Submittal
Design Review Board Submittal
Date: 01/31/2024