Existing RM1 Zoning Regulations and Proposed NCD Regulations

		EXISTING (NB LOCAL HD)	PROPOSED NCD
LOT COVERAGE		45%	NA
SETBACKS	FRONT	20'-0"	North Shore -10'-0" Biscayne Beach - 10'-0" Normandy Isle and Normandy Shores - 20'-0" Waterfront - 25'-0"
	INTERIOR SIDE	< 65 Width - 7.5 feet > 65 Width - 10 feet / or 8% of lot width (whichever is greater)	North Shore, Biscayne Beach, Normandy Isle and Normandy Shores Non-Waterfront: •Lot width of 60 feet or less - 5 feet •Lot width of 61 feet or greater - 7.5 feet, or 8% of lot width Waterfront: •7.5 feet, or 8% of lot width, whichever is greater •One (1) interior side shall be 10 feet -or- 10% of lot width
	SIDE FACING A STREET	< 65 Width - 7.5 feet > 65 Width - 10 feet / or 8% of lot width (whichever is greater)	Five (5) feet
	SUM OF THE SIDES	16% of lot width	NA
	REAR	10% of lot depth	North Shore •Non-waterfront lots – 5 feet •Waterfront lots – 10% of lot depth <u>Biscayne Beach</u> •10 % of lot depth <u>Normandy Isle and Normandy Shores</u> •Non-waterfront lots – 5 feet •Waterfront -10% of lot depth, maximum 20 feet
NON-CONFORMING SETBACK STANDARDS		N/A	Existing 'Contributing' Buildings •Rooftop additions may follow existing interior side and/or rear setbacks •New ground level additions may follow any existing interior side and/or rear setback, provided at least 33 % of building issubstantially retained and restored

Existing RM1 Zoning Regulations and Proposed NCD Regulations

	EXISTING	
	(NB LOCAL HD)	PROPOSED NCD
MAXIMUM LOT AGGREGATION	Two (2) contiguous lots* *The two (2) lot aggregation may be exceeded if the development site was combined with a unity of title prior to June of 2017	Two (2) platted lots Three (3) platted lot Exceptions: •Where a development site contains at least one (1) 'contributing' structure •Projects consisting solely of affordable and/or workforce housing
MAXIMUM HEIGHT	50'-0"	 Three (3) stories / 30 feet for the first 30 feet of buildingdepth Four (4) stories / 40 feet for the remainder of the lot depth Five (5) stories and 50 feet may be permitted by DRB or HPB for the remainder of the lot depth for properties that contain at least one (1) 'contributing' building that is 50% or more substantially retained and restored* NOTE: The Design Review Board may waive the aforementioned requirement for the 50% retention of existing 'contributing' buildings, provided at least 25% of all existing 'contributing' buildings on site, as measured from the front elevation, are substantially retained and restored. *Revised as recommended in draft ordinance for LUDC
UNIT SIZE	MINIMUM UNIT SIZE New construction: 550 Rehabilitated buildings: 400 WF/AH: 400 AVERAGE UNIT SIZE New construction: 800 Rehabilitated buildings: 500 WF/AH: 400	 MINIMUM UNIT SIZE New construction - 400 'Contributing' buildings which are substantially retained and restored - 300 Additions to 'contributing' buildings which are substantially retained and restored - 300 WF/AH - 400 AVERAGE UNIT SIZE New construction - 500 'Contributing' buildings which are substantially retained and restored - 400 Additions to 'contributing' buildings which are substantially retained and restored - 400 WF/AH - 400

Existing RM1 Zoning Regulations and Proposed NCD Regulations

	EXISTING	
	(NB LOCAL HD)	PROPOSED NCD
PARKING	Lots 65 feet in width or less: • No Parking Requirement Lots wider than 65 feet: •Units between 550 and 1,600 SF - 1 (one) space per unit •Units 1,600 SF or greater - 2 (two) spaces per unit	Lots 65 feet in width or less; Development sites with six (6) units or less (regardless of lot width); 'Contributing' buildings that are substantially retained, preserved and restored: • No Parking Requirement Lots wider than 65 feet: One (1) space per unit (regardless of unit size) Note: Design Review Board can waive parking requirements
DEMOLITION PROCEDURES	Subject to HPB approval	 No demolition of 'contributing' buildings for surface parking lots Requirements for replacement structure prior to demolition of 'contributing' building
ROOF-TOP ADDITIONS	Subject to HPB approval	May be reviewed by staff, subject to compliance with specified criteria
ELEVATOR AND STAIRWELL BULKHEAD HEIGHT	Subject to HPB approval	Required to meet, unless waived by DRB
SHADE STRUCTURE HEIGHT EXCEPTION	Subject to HPB approval, not to exceed 25'	Maximum 10' and subject to DRB approval
DESIGN AND RESILIENCY STANDARDS SPECIFIC TO NB NCD	Not required, but still subject to applicable Sea Level Rise Criteria	As specified in ordinance
ADDITIONAL PARKING DESIGN STANDARDS SPECIFIC TO NB NCD	Not required	As specified in ordinance