
— EXISTING I.D. SIGN DROPPED CONC. SIDE-WALK AND CURB TO BE REMOVED (TYP.) EXISTING AUTOMOTIVE ACCESSORY SALES & AUTOMOTIVE REPAIR BUILDING TO BE MODIFIED 1,746 SQ. FT. 100.00 EXISTING CONC. PAVEMENT (TYP.) 20% - LINE OF EXISTING CANOPY ABOVE (TYP.) EXISTING CONC. SIDE-WALK TO BE REMOVED (TYP.) - EXISTING OIL RECYCLING TANK TO BE RELOCATED EXISTING QUEEN PALM EXISTING IN A PLIANTER SIDEWALK (TYP.) EXISTING CONC.
SIDEWALK (TYP.) - EXISTING PLANTER - EXISTING QUEEN EXISTING TRASH PALMS IN POOR CONDITION ENCLOSURE TO BE REMOVED (TYP.) EXISTING FUEL TO BE RELOCATED DISPENSER — EXISTING — EXISTING CONC. CURB TO BE REMOVED LIGHT POLE (TYP.) - EXISTING WINDMILL PALM IN A PLANTER 100.00 - EXISTING COCOPLUM 10' ALLEY TO BE REMOVED (TYP.) 75.00' — EXISTING U.G. FUEL STORAGE TANKS (TYP.) EXISTING QUEEN STRUCTURE PALMS TO BE REMOVED (TYP.) **EXISTING BUILDING** TO BE MODIFIED 1,624 SQ. FT. AREA (TYP.) EXISTING CONC.
PAVEMENT (TYP.) EXISTING DROPPED CONC. SIDE-WALK AND CURB PLANTER (TYP.) TO BE REMOVED (TYP.) ALLEY EXISTING FUEL DISPENSER 202 - EXISTING QUEEN PALM TO BE REMOVED EXISTING H.C. RAMP AND CONC. LINE OF EXISTING SIDE WALK CANOPY ABOVE TO BE REMOVED EXISTING H.C. PARKING TO BE REMOVED-CONC. CURB EXISTING POLE - EXISTING LIGHT (TYP.) — I.D. SIGN EXISTING 2' CONC. CURB AND GUTTER -EXISTING LANDSCAPE AREA (TYP.) 75.00' COCOPLUM TO BE REMOVED - EXISTING EXISTING TRANSFORMER FIRE HYDRANT — PAD EXISTING SIDEWALK (TYP.) **EXISTING / DEMOLITION SITE PLAN** 



## LOCATION MAP

SCALE: NTS



<u>LEGAL DESCRIPTION:</u>
LOTS 5 THROUGH 8, BLOCK 1, "NORMANDY BEACH SOUTH", ACCORDING TO THE PLAT THEREOF, AS RECORDED IN PLAT BOOK 21, PAGE 54, OF THE PUBLIC RECORDS OF MIAMI-DADE COUNTY, FLORIDA.

<u>LEGAL DESCRIPTION:</u>
LOTS 9 THROUGH 11, BLOCK 7, "NORMANDY BEACH SOUTH", ACCORDING TO THE PLAT THEREOF, AS RECORDED IN PLAT BOOK 21, PAGE 54, OF THE PUBLIC RECORDS OF MIAMI-DADE COUNTY, FLORIDA.

## **DEMOLITION NOTES:**

1.) CONTRACTOR TO CUT AND CAP EXITING SANITARY SEWER PIPING AND WATER PIPING AS PER NEW CONNECTIONS AND AS REQUIRED BY LOCAL AND STATE REGULATORS.

2.) COORDINATE WITH F.P.L. RELOCATION OF F.P.L. POWER POLE AS REQUIRED AND REMOVAL OF SEVICE DROP INTO EXISTING BUILDING PRIOR TO DEMOLITION.


3.) FIELD VERIFY DISCONNECTION OF POWER BEFORE DEMOLITION.


4.) COORDINATE WITH ARCHITECTURAL DWG'S AND STRUCTURAL DWGS. FOR SIZE, LOCATION, SHORING AND OR BRACING REQUIRED FOR ALL DEMOLITION WORK.

5.) COORDINATE WITH OWNER FOR DISPOSAL OF DEMOLISHED DEBRIS.

6.) AS PER F.B.C. 105.9. THE ENFORCING AGENCY SHALL REQUIRE EACH BUILDING PERMIT FOR THE DEMOLITION OR RENOVATION OF AN EXISTING STRUCTURE TO CONTAIN AN ASBESTOS NOTIFICATION STATEMENT WHICH INDICATES THE OWNER'S OR OPERATOR'S RESPONSIBILITY TO COMPLY WITH THE PROVISIONS OF SECTION 469.003, FLORIDA STATUTES, AND TO NOTIFY THE DEPARTMENT OF ENVIRONMENTAL PROTECTION OF HIS OR HER INTENTIONS TO REMOVE ASBESTOS, WHEN APPLICABLE, IN ACCORDANCE WITH STATE AND FEDERAL LAW.

Unidad of Miami Beach





SYMBOL USED ON PLAN			PLANT NAME			VE CIES	CALIPER	HEIGHT		CANOPY DIAMETER	QUANTITY
SYMBOL	INEW	EXIST	SCIENTIFIC	COMMON	YES	I NO	INST.	INST.	MATURE	MATURE	
Co P	•		Coccoloba diversifolia	PIGEON PLUM	•		3" MIN	12'-0"	15' – 25'	20' - 30'	3
	•		Swietenia mahagoni	MAHOGANY	•		3" MIN	12' – 14'	15' – 25'	20' – 25'	2
SIN CH	•		Veitchia merrillii	CHRISTMAS PALM		•	2" MIN	5' – 8'	20' - 30"	10'-0"	6
			Thrinax radiata	THATCH PALM	•		N/A	10"	15 '- 20'	12'-0"	1
	•		Jasminium volubile	WAX JASMINE		•	N/A	18"	24"	N/A	178 @ 24 0.4
PEI	•		Arachis glabrata	PERENNIAL PEANUT	•		N/A	N/A	N/A	N/A	70 AT 18"O.

İ	LEGAL DESCRIPTION: LOTS 9 THROUGH 11, BLOCK 7, "NORMANDY BEACH SOUTH", ACCORDING TO THE PLAT THEREOF, AS RECORDED IN PLAT BOOK 21, PAGE 54, OF THE PUBLIC RECORDS OF MIAMI-DADE COUNTY, FLORIDA.
	LANDSCAPE LEGEND

SYMBOL USED ON PLAN		PLANT NAME		NATI SPEC		CALIPER	HEIGHT		CANOPY DIAMETER	QUANTITY	
SYMBOL	NEW	EXIST	SCIENTIFIC	СОММОИ	YES	I NO	INST.	INST.	MATURE	MATURE	
PA PA	•		Acoelorrhaphe wrightii	PAUROTIS PALM	•		2" MIN	5' – 8'	8' - 9'	12'-0"	1 (CLUMP)
TH.	•		Thrinax radiata	THATCH PALM	•		6"	8'–10'	15'- 20'	12'-0"	4
CP	•		Chrysobalanus icaco	HORIZONTAL COCO PLUM	•		N/A	24"	NA	N/A	217 @ 24" O.C 2 GAL.
PER	•		Arachis glabrata	PERENNIAL PEANUT		•	N/A	FULL	N/A	N/A	224 AT 12"O.C. 1 GAL.


VENUE


ABBOTT

100.00'


PROPOSED CAR WASH 600 SQ. FT.








- THIN BRANCHES AND FOLIAGE AS DIRECTED BY LANDSCAPE ARCHITECT.





## GENERAL NOTES

1- THE LANDSCAPE CONTRATOR IS TO LOCATE AND VERIFY ALL UNDERGROUND AND OVERHEAD UTILITIES PRIOR TO BEGINING WORK CONTACT PROPER UTILITY COMPANIES AND GENERAL CONTRACTOR PRIOR TO DIGGING FOR FIELD VERIFICATION. THE OWNER AND THE ARCHITECT SHALL NOT BE RESPONSIBLE FOR ANY DAMAGES TO UTILITY OR IRRIGATION LINES ( SEE ROADWAY PLANS FOR MORE UTILITY NOTES).

2- LANSCAPE CONTRACTOR IS TO VERIFY ALL CURRENT DRAWINGS AND CHECK FOR DISCREPANCIES AND BRING THEM TO THE ATTENTION OF THE ARCHITECT PRIOR TO COMMENCING WITH THE WORK.

3- ALL UNATTENDED AND UNPLANTED TREE PITS ARE TO BE PROPERLY BARRICADED AND FLAGGED DURING INSTALLATION.

4- ALL PLANTING PLANS ARE ISSUED AS DIRECTIVES FOR SITE LAYOUT. ANY DEVIATIONS, SITE CHANGES, ETCETERA, ARE TO BE BROUGHT TO THE ATTENTION OF THE ARCHITECT FOR CLARIFICATION PRIOR TO

5- ALL PROPOSED TREES TO BE RELOCATED SHALL BE ROOT PRUNED 8 WEEKS PRIOR TO CONSTRUCTION AND DONE ACCORDING TO GOOD NURSERY PRACTICE AS REQUIRED. TRENCH DEPTH SHALL BE 18'-36"± ROOT BALL SHALL BE A MINIMUM OF 60" WHEN ROOT PRUNED. FILL TRENCH WITH FIBROUS-MATERIAL SUCH AS LEAVES OR WOOD SHAVINGS. WATERING SHALL BE ONCE A WEEK DURING ROOT PRUNING. TORN ROOTS SHALL BE TRIMMED TO SOLID WOOD. RELOCATED TREE SHALL BE LIGHTLY PRUNED BY HAND.

6- ALL EXISTING TREES SHALL COMPLY WITH THE "AMERICAN NATIONAL STANDARD INSTITUTE, (ANSI) 300-1995." CURRENT EDITION RESPECTIVELY.

1- LANDSCAPE CONTRACTOR SHALL WATER RELOCATED TREES WITH TEMPORARY IRRIGATION EVERYDAY FOR THE FIRST MONTH THEN 2-3 TIMES A WEEK UNTIL SYSTEM IS FULLY AUTOMATIC: OWNER TO SUPPLY WATER ON SITE.

8- EXISTING TREES TO BE BARRICADED PRIOR TO BEGINNING OF CONSTRUCTION & SHALL REMAIN IN PLACE DURING CONSTRUCTION.

9- NO HEAVY EQUIPMENT, CONSTRUCTION MATERIALS OR SOIL DEPOSITS ARE TO BE ALLOWED INSIDE

10- TOPSOIL SHALL BE CLEAN & REASONABLY FREE OF CONSTRUCTION DEBRIS, WEEDS, ROCKS, & NOXIOUS PESTS

II- TREE REMOVAL PERMIT SHALL BE REQUIRED PRIOR TO CONSTRUCTION & ANY CLEARING OPERATIONS AS REQUIRED.

12- PROVIDE A 3' HIGH PROTECTIVE BARRIER AS APPROVED BY LOCAL CODE.

13- ALL PLANT MATERIAL IS TO BE FLORIDA NUMBER I OR BETTER PURSUANT TO THE FLORIDA DEPARTMENT OFAGRICULTURE'S GRADES AND STANDARDS FOR NURSERY PLANTS.

14- SOD IS TO BE GRADE "A" WEED FREE.

15- ALL AREAS MARKED "LAWN" SHALL BE SOLID SODDED "ST. AUGUSTINE FLORATAM" SOLID SOD. ALL SOD IS TO BE LAID LEVEL, TIGHT, AND CUT EVEN ALONG PLANTING BEDS.

16- ALL PLANTS ARE TO BE TOP DRESSED WITH A MINIMUM 3" LAYER OF MELALEUCA MUICH, EUCALYPTUS MUICH OR EQUAL.

17- PLANTING PLANS SHALL TAKE PRECEDENCE OVER PLANT LIST IN CASE OF DISCREPANCIES.

18- NO CHANGES ARE TO BE MADE WITHOUT THE PRIOR CONSENT OF THE ARCHITECT AND OWNER ADDITIONS AND / OR DELETIONS TO THE PLANT MATERIAL MUST BE APPROVED BY THE ARCHITECT.

19- LANDSCAPE CONTRACTOR IS RESPONSIBLE FOR PROVIDING THEIR OWN SQUARE FOOTAGE TAKEOFFS AND FIELD VERIFICATIONS FOR 100% SOD COVERAGE FOR ALL AREAS SPECIFIED.

20- ALL LANDSCAPE AREAS ARE TO BE PROVIDED WITH AUTOMATIC SPRINKLER SYSTEM WHICH WILL PROVIDE 100% COVERAGE , AND 50 % OVERLAP.

21- ALLTREES IN LAWN AREAS ARE TO RECIEVE A 24" DIAMETER MUICHED SAUCER AT THE BASE OF THE

22- ALL LAWN LOCATED IN PARKING ISLANDS AFTER SOIL IS BROUGHT UP TO GRADE. DEEPLY SET ROOT BALLS ARE NOT ACCEPTABLE.

23- PLANTING SOIL FOR TOPSOIL AND BACKFILL SHALL BE 50/50 MIX, NEMATODE FREE BY MORRIS

MAGIC SOIL, HIALEAH, FLORIDA. PLANTING SOIL FOR ANNUAL BEDS TO BE COMPRISED OF 50 % CANADIAN PEAT MOSS, 25% SALT FREE COARSE SAND AND 25 % AEROLITE.

24- TREE AND SHRUB PITS WILL BE SUPPLEMENTED WITH "AGRIFORM PELLETS", 21 GRAM SIZE WITH A 20-10-5 ANALYSIS, OR SUBSTITUTE APPLICATION ACCEPTED BY ARCHITECT. DELIVER IN MANUFACTURER'S STANDARD CONTAINERS SHOWING WEIGHT, ANALYSIS AND NAME OF MANUFACTURER

## 25 - MAINTENANCE

- A. BEGIN MAINTENANCE IMMEDIATELY AFTER PLANTING.
- B. MAINTAIN TREES, PALMS, SHRUBS AND OTHER PLANTS UNTIL FINAL ACCEPTANCE BUT IN NO CASE LEGS THAN FOLLOWING PERIOD: 30 DAYS AFTER SUBSTANTIAL COMPLETION OF PLANTING.
- C. MAINTAIN TREES, PALMS, SHRUBS AND OTHER PLANTS BY PRUNING, CULTIVATING AND WEEDING AS REQUIRED FOR HEALTHY GROWTH. RESTORE PLANTING SAUCERS. TIGHTEN AND REPAIR STAKE AND GUY SUPPORTS AND RESET TREES AND SHRUBS TO PROPER GRADES OR VERTICAL POSITION AS REQUIRED. RESTORE OR REPLACE DAMAGED WRAPPINGS. SPRAY AS AS REQUIRED TO KEEP TREES AND SHRUBS FREE OF INSECTS AND DISEASES.
- D. REMOVE AND REPLACE EXCESSIVELY PRUNED OR MISFORMED STOCK RESULTING FROM
- E. MAINTAIN LAWNS FOR NOT LESS THAN THE PERIOD STATED BELOW, AND LONGER AS REQUIRED TO ESTABLISH AN ACCEPTABLE LAWN.
- 1. SODDED LAWNS, NOT LESS THAN 30 DAYS AFTER SUBSTANTIAL COMPLETION. 2. SEEDED LAWNS, NOT LESS THAN 60 DAYS AFTER SUBSTANTIAL COMPLETION.
- F. MAINTAIN LAWNS BY WATERING FERTILIZING, WEEDING, MOVING, TRIMMING, AND OTHER OPERATIONS SUCH AS ROLLING, REGRADING AND REPLANTING AS REQUIRED TO ESTABLISH A SMOOTH, ACCEPTABLE LAWN , FREE OF ERODED OR BARE AREAS.
- G. LANDSCAPE CONTRACTOR IS RESPONSIBLE FOR WATERING ALL SOD AND PLANT MATERIALS FROM DAY OF INSTALLATION THROUGH FINAL ACCEPTANCE EVEN IF IRRIGATION IS NOT IN PLACE, UNLESS THIS RESPONSIBILITY IS ASSUMED IN WRITING BY ANOTHER PARTY.